

DAYTONA Vlies

Manufacturing process	Tufted	ISO 2424
Gauge	1/4" Loop	
Pilecomposition	100% PP	ISO 2424
Primary backing	Woven PP	ISO 2424
Secondary backing	Starback + Felt	ISO 2424
Width	400 cm	± 1% EN 986
Pile weight	approx. 1400 gr/m ²	ISO 8543
Total weight	Starback : approx. 2705 gr/m ² Felt : approx. 2834 gr/m ²	± 15% ISO 8543
Pile height	approx. 9,0 mm	ISO 1765
Total height	Starback : approx. 11,7 mm Felt : approx. 13,9 mm	+ 15% / -10% ISO 1765
Number of knots	approx. 74.260 /m ²	+ 10% / -7,5% ISO 1763
Fire classification	Starback : Efl (EN13501-1) Felt : Efl (EN13501-1)	EN 13501-1
Light fastness	≥ 5	105-B02
Wearability	≥ 4,5	105-X12
Water fastness	≥ 4,5	105-E01
Thermal resistance	0,17 m ² K/W	ISO 8302
Sound isolation	25 dB	ISO 10140
GUT Nr.	Starback : 7FA8BDBB Felt : DD4B8841	

Floorsymbols Felt



Floorsymbols Starback



Certificates

