

Dimension
304,8
*
609,6
mm

Dimension
177,8
*
1219,2
mm

Thickness
2,5 mm
Wear layer
0,3 mm

Weight
4,79
kg/m²

AMT/Box
3,716 m²
AMToPCS/BOX
20 PCS

AMT/Box
2,601 m²
AMToPCS/BOX
12 PCS

Linofloor

HIGH QUALITY

fortress

DESCRIPTION

Constraction		Luxury Vinyl Tile
Dimension	ISO 24342	304,8' 609,6 mm 177,8x1219,2 mm
Total thickness	ISO 24346	2,5 mm
Wear layer thickness	ISO 24340	0,3 mm
Total weight	ISO 23997	4,79 kg/m ²
Amount per box		3,716m ² / 2.601m ²
Amount of pieces per box		20 / 12 pieces
Amount per pallet		252,70m ² / 208,08m ²

CLASSIFICATION

European classification	ISO 10582	class: 23/31
-------------------------	-----------	--------------

PERFORMANCE

Abrasion group	EN 660-2	class: T
Residual indentation after exposure to heat	EN 433:94	max. ≤ 0,2 mm
Dimensional stability and curling after exposure to heat(60-C/6Hr)	EN 434:94	≤ 0,15 %
Thermal resistance		0,22 W/m K
Fire resistance	EN 13501-1	Bf1 - s1
Electrical resistance	EN 1081	√
Castor chair testing	EN 425	√
Chemical resistance	EN 423:93	Class 0
Slip resistance	EN 13893	class: DS
Formaldehyde emission	ASTM D570-98	E0 (no any Formaldehyde)
Content of PCP	EN 12673	does not contain
VOC emission	DIN EN ISO16000	Pass

