

## Xtrafloor® Base

PRODUCT INFORMATION		
Composition	Permanent resilient underlay including mineral fillers and polyurethane binder	
Thickness	1.5mm	
SIZE & PACKING		
Roll format	Approx. 10m x 1m (10m <sup>2</sup> per roll)	
Weight per sqm	1.5kg/m <sup>2</sup>	
Weight per roll	15kg/roll	
TEST RESULTS		
Inflammability	EN 13501	Bfl-S1
Impact sound reduction in combination with 4.5mm Click LVT	EN ISO 10140-3	ΔLw= 13dB
Thermal resistance R	DIN 52616	0.01m <sup>2</sup> K/W
Underfloor heating	EN 12524	Suitable, max. 27° C



## Xtrafloor® Silent

PRODUCT INFORMATION		
Composition	Extruded closed cell polyolefin foam	
Thickness	1.1mm	
SIZE & PACKING		
Roll format	Approx. 12.5m x 1m (12.5m <sup>2</sup> per roll)	
Weight per sqm	0.26kg/m <sup>2</sup>	
Weight per roll	3.25kg/roll	
TEST RESULTS		
Inflammability	EN 13501	Bfl-S1
Impact sound reduction in combination with 4.5mm Click LVT	EN ISO 10140-3	ΔLw= 21dB / ΔLlin = 10dB
Thermal resistance R	DIN 52616	0.027m <sup>2</sup> K/W
Underfloor heating	EN 12524	Suitable, max. 27° C

